

FIREBOX T35 & T55

Available with optional integrated wireless module
Up to 523 Mbps UTM throughput, 5 x 1Gb ports



BIG SECURITY FOR SMALL BUSINESSES

Perfect as a stand-alone solution for a small office, Firebox® T35 and T55 appliances are also ideal for larger organizations that want to extend easy-to-use, full Unified Threat Management (UTM) protection for smaller sites. With more features than any other UTM firewall in its market, these appliances are small, cost-effective security powerhouses that deliver nearly every feature present in WatchGuard's higher end UTM appliances, including all security services in the WatchGuard Total Security Suite.

“

By standardizing on WatchGuard for network security, we were able to decrease the average installation time by more than 75 percent - now averaging anywhere from 15-20 [minutes] per site. We just plug the appliance in, it establishes a connection and pulls the configuration file. We are then up and running, and free to focus our time on testing credit card processing and access to approved web sites.

~ Dustin McCreight, Product Manager, Network and Security Services, NCR Corporation

”

TOTAL NETWORK PROTECTION

Small businesses and remote locations have long been thought of as soft targets for attackers. WatchGuard Firebox T35 and T55 tabletop appliances bring enterprise-level network security to those small office/branch office and small retail environments that matches the reality of today's distributed work style. Our unique product architecture enables smaller businesses to leverage best-in-class security services – from URL filtering and intrusion prevention to application control and data loss prevention – minus the cost and complexity of managing multiple single-point solutions.

QUICK AND SIMPLE DEPLOYMENT

Cloud-based RapidDeploy technology, a configuration and deployment tool that comes standard with WatchGuard Firebox appliances, enables IT staff to create and store configuration data in the cloud – public or private – and have a new appliance directly shipped to its destination. Once the device arrives, it can connect to the cloud for a secure download of its configuration settings, saving staff travel time and money. This technology is particularly advantageous for large distributed enterprises where managing a multitude of devices efficiently across multiple locations and geographies is critical.

EASY TO MANAGE AND UNDERSTAND

Firebox T Series appliances are not only easy to initially configure and deploy, they are also designed with an emphasis on centralized management, making ongoing policy and network management simple and straightforward. WatchGuard Dimension, which is included with purchase, provides a suite of big data visibility and reporting tools that instantly identify and distill key network security threats, issues and trends so you can take immediate preventive or corrective action. Security is complex, running it doesn't have to be.

FEATURES & BENEFITS


- Wireless versions of the T35 and T55 use 802.11ac operating in the 2.4 GHz and 5GHz bands for high performance and superior reliability.
- All logging and reporting functions included with purchase, with over 100 dashboards and reports including PCI and HIPAA.
- 5 Gigabit Ethernet ports support high-speed LAN backbone infrastructures & gigabit WAN connections.
- PoE port to power a peripheral device such as a WatchGuard Secure Wi-Fi Access Point, allowing administrators to extend the reach of their networks without having to run costly AC power to the remote device.

Firebox T Series

T35/T35-W

T55/T55-W

THROUGHPUT		
Firewall	940 Mbps	1 Gbps
Firewall (IMIX)	480 Mbps	500 Mbps
VPN (UDP 1518)	560 Mbps	360 Mbps
VPN (IMIX)	96 Mbps	148 Mbps
Antivirus	325 Mbps	636 Mbps
IPS (fast/full scan)	573 / 300 Mbps	636 / 444 Mbps
UTM (fast/ full scan)	278 / 203 Mbps	523 / 378 Mbps
CAPACITY		
Interfaces 10/100/1000*	5	5
I/O interfaces	1 SRL/2 USB	1 SRL/2 USB
PoE ports	1	1
Concurrent connections	1.3 M	1.3 M
Concurrent connections (proxy)	135,000	135,000
New connections per second	6,800	9,500
VLANs	50	75
WSM licenses (incl)	0	0
TDR Host Sensors included	20	35
Authenticated users limit	200	200
VPN TUNNELS		
Branch Office VPN	25	40
Mobile VPN	25	50
SECURITY FEATURES		
Firewall	Stateful packet inspection, deep packet inspection, proxy firewall	
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3, SMTP, IMAP, and Explicit Proxy	
Threat protection	DoS attacks, fragmented & malformed packets, blended threats & more	
VoIP	H.323, SIP, call setup and session security	
Filtering options	Browser Safe Search, Google for Business	
VPN & AUTHENTICATION		
Cloud providers	AWS (Static/Dynamic), Azure (Static/Dynamic)	
Encryption	AES 256-128 bit, 3DES, DES	
IPSec	SHA-2, IKEv1/v2, IKE pre-shared key, 3rd party cert	
Single sign-on	Windows, Mac OS X, mobile operating systems, RADIUS	
Authentication	RADIUS, LDAP, Windows Active Directory, VASCO, RSA SecurID, internal database, Duo, SMS Passcode	
MANAGEMENT		
Logging and notifications	WatchGuard, Syslog, SNMP v2/v3	
User interfaces	Centralized console (WSM), Web UI, scriptable CLI	
Reporting	WatchGuard Dimension includes over 100 pre-defined reports, executive summary and visibility tools	
CERTIFICATIONS		
Security	Pending: CC EAL4+, FIPS 140-2	
Safety	NRTL/C, CB	
Network	IPv6 Ready Gold (routing)	
Hazardous substance control	WEEE, RoHS, REACH	
NETWORKING		
Routing	Static, Policy-based routing (BGP4, OSPF, RIP v1/v2),	
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS	
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based	
Wireless	Optional integrated 802.11ac dual band 2.4 GHz and 5 GHz Wi-Fi module	



PHYSICAL AND POWER SPECIFICATIONS

Product Dimensions	8" x 8.5" x 1.8" (205.5mm X 217mm x 48mm)
Shipping Dimensions	12.1" x 10.2" x 7.2" (308x261x181 mm)
Shipping Weight	6.2 lbs (2.8 kg)
AC Power	100-240 VAC Autosensing
Power Consumption	12W, Max 15W
Power over Ethernet	802.3at(PoE+) at 25 W

ENVIRONMENT	OPERATING	STORAGE
Temperature	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C
Relative Humidity	5% to 90% non-condensing	5% to 90% non-condensing
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)
MTBF	T35/T35-W 499,632 hours at 25 C T55/T55-W 422,351 hours at 25 C	

STRONG SECURITY AT EVERY LAYER

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing and much more. Total and Basic Security Suite packages are available on all Firebox solutions.

Product	TOTAL SECURITY SUITE	Basic Security Suite
Intrusion Prevention Service (IPS)	✓	✓
App Control	✓	✓
WebBlocker	✓	✓
spamBlocker	✓	✓
Gateway AntiVirus	✓	✓
Reputation Enabled Defense (RED)	✓	✓
Network Discovery	✓	✓
APT Blocker	✓	
Data Loss Protection (DLP)	✓	
Dimension Command	✓	
Threat Detection & Response	✓	
Support	Gold (24x7)	Standard (24x7)

Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. You can also refer to the Appliance Sizing Guide at www.watchguard.com/sizing.

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895
WEB www.watchguard.com