# WatchGuard<sup>®</sup> XTM 3 Series

#### WITH A NEXT-GENERATION XTM 3 SERIES SECURITY SOLUTION, YOUR NETWORK IS:

#### **SECURE**

- Application-layer content inspection recognizes and blocks threats that stateful packet firewalls cannot detect.
- Wide-ranging proxy protection provides robust security on HTTP, HTTPS, FTP, SMTP, POP3, DNS, TCP/UDP.
- A suite of security subscriptions boosts protection in critical attack areas for complete threat management.
- Optional Application Control keeps unproductive, inappropriate, and dangerous apps off-limits.

#### **FAST and EFFICIENT**

- Up to 1.4 Gbps firewall throughput and up to 240 Mbps VPN throughput keep data moving.
- Up to seven 1GgE ports support high-speed LAN backbone infrastructures and gigabit WAN connections.
- Interactive, real-time monitoring and reporting at no additional charge give an unprecedented view into network security activity so you can take immediate preventive or corrective actions.
- Includes the "Pro" version of the Fireware® XTM operating system for advanced networking features, including VLAN support, multi-WAN load balancing, and dynamic routing.
- Intuitive management console centrally manages all security functions.
- Role-based access control (RBAC) allows lead administrators to create custom roles for granular control.
- Drag-and-drop Branch Office VPN setup three clicks and your remote office is connected.

#### **FLEXIBLE**

- WAN and VPN failover provide redundancy for increased reliability.
- Multiple VPN choices (IPSec, SSL, L2TP) deliver flexibility in remote access, including support for Android and Apple iOS devices.
- To maximize port utilization, any of the ports can be configured as Trusted, External, or DMZ.
- Choose the form factor that suits your needs XTM 330 is rack mount, XTM 33/33-W is tabletop.

#### WIRED OR WIRELESS – YOUR CHOICE

- The XTM 33-W wireless model includes optional dual-band 802.11/n technology for much more responsive wireless network connections and expanded range. Allows users to access 2.4 GHz or less crowded 5 GHz band.
- Multiple security zones give administrators precise control over Internet access privileges for different user groups.
- Wireless guest services segment the Internet for customers/guests.

#### **PREPARED FOR TOMORROW'S CHALLENGES**

- Multi-layered, interlocking security protects the network while throughput remains high. No need to compromise protection for strong performance or vice versa.
- Advanced networking features ensure reliability and the flexibility to meet changing business requirements.
- Secure remote connectivity keeps the mobile workforce online and productive.
- Monitoring and reporting tools, included at no extra cost, support industry and regulatory compliance, with drill-down functions that make it easy to pinpoint specific activities.

#### **RECOMMENDED FOR** SMALL BUSINESSES AND BRANCH OFFICES

MatchGuard

Datasheet

WatchGuard XTM 3 Series appliances deliver a new class of performance-driven security for growing businesses. The XTM 3 Series offers up to 1.4 Gbps firewall throughput and security features including full HTTPS inspection, VoIP support, and optional application control.

#### WHY BUY AN ALL-IN-ONE SOLUTION?

An all-in-one XTM network security solution integrates complete protection while slashing the time and cost associated with managing multiple single-point security products. All security capabilities work together for a holistic, comprehensive approach to network protection. Your IT staff has more time to focus on other areas of network administration, and your business saves money on support and hardware costs.

# "WatchGuard makes a great firewall and security appliance, and backs it up with tremendous and personal support."

Chet Cromer President C2IT Consulting, Inc



	ard		
WatchGu			
		I	l
XTM 3 SERIES	XTM 33	XTM 33-W	XTM 330
THROUGHPUT & CONNECTIO			
Firewall throughput*	850 Mbps	850 Mbps	1.4 Gbps
VPN throughput*	100 Mbps	100 Mbps	240 Mbps
AV throughput*	175 Mbps	175 Mbps	340 Mbps
IPS throughput*	328 Mbps	328 Mbps	640 Mbps
UTM throughput* Interfaces 10/100/1000	146 Mbps	146 Mbps	298 Mbps
nterfaces 10/100/1000	5 copper 1 Serial	5 copper 1 Serial	7 copper 1 Serial
/O interfaces	1 USB	1 USB	2 USB
Vodes supported (LAN IPs)	Unrestricted	Unrestricted	Unrestricted
Concurrent connections	40,000	40,000	40,000
bi-directional) lew connections per second	3,800	3.800	5,500
/LANs	-,		
oridging, tagging, routed mode	75	75	75
Authenticated users limit	500	500	500
WSM licenses (incl)	4	4	4
Nireless available	-	802.11a/b/g/n	-
/PN TUNNELS			
Branch Office VPN	50	50	50
Mobile VPN IPSec (incl/max)	5/55	5/55	5/55
Mobile VPN SSL / L2TP	55	55	55
SECURITY FEATURES			
Firewall		pection, deep pack	et inspection,
Application proxies	proxy firewall HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3		
Threat protection	Blocks spyware, DoS attacks, fragmented packets,		
	malformed packets, blended threats, and more		
/oIP	H.323, SIP, call setup and session security		
ecurity subscriptions	Application Control, Intrusion Prevention, Gateway AV, Reputation Enabled Defense, WebBlocker, spamBlocker		
/PN & AUTHENTICATION		9 100 0FC	
ncryption PS or	DES, 3DES, AES 128-, 192-, 256-bit		
PSec (PN failurer	SHA-1, MD5, IKE pre-shared key, 3rd party cert		
/PN failover SL	Yes		
2TP	Thin client Works with native OS clients		
221P PPTP			
	Server and Passthrough		
iingle sign-on (AUTH	Transparent Active Directory Authentication		
Norn Other user authentication	RADIUS, LDAP, Secure LDAP, Windows Active Directory VASCO, RSA SecurID, web-based, local, Microsoft		
	Terminal Services		,
MANAGEMENT			
Management platform	WatchGuard System Manager (WSM) v11 or higher		
Alarms and notifications	SNMP v2/v3, Email, Management System Alert		
erver support	Logging, Reporting, Quarantine, WebBlocker, Management		
Veb UI	Supports Window		
Command line interface	Includes direct co	nnect and scripting	
STANDARD NETWORKING	0		
los		DiffServ, modified s	
P address assignment	Static, DHCP (serv	er, client, relay), PPP	oE, DynDNS
CERTIFICATIONS			2
Security	ICSA Firewall, ICSA VPN, EAL4+, FIPS 140-2		
Safety	NRTL/C, CB		
Network	IPv6 Ready Gold (ro	<u>.</u>	-
Control of hazardous substances	WEEE, RoHS, REACH		
'Throughput rates will vary ba	ased on environment	and configuration. Co	ntact

# **ADVANCED NETWORKING**

XTM 3 Series appliances ship with the Proversion of the Fireware XTM operating system. Advanced networking features<sup>+</sup> include:

Routing	Static / Dynamic (BGP4, OSPF, RIP v1/v2) / Policy-based	
High Availability	Active/passive, active/active with load balancing	
NAT	Static, dynamic, 1:1, IPSec traversal	
Link Aggregation	802.3ad dynamic, static, active/backup	
Other Features	High Availability, Port Independence, WAN failover, Multi-WAN load balancing, Transparent/drop-in mode	

<sup>†</sup> Server load balancing is not available on 3 Series appliances.

### **DIMENSIONS AND POWER**

51,644 hours @ 77° F (25° C)		
129,955 hours @ 104° F(40° C)		
0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)	
0 to 9,843 ft @ 95° F (3,000 m @ 35° C)	0 to 15,000 ft @ 95° F (4,570 m @ 35° C)	
10% to 85% non-condensing	10% to 95% non-condensing	
32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C	
32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C	
OPERATING	STORAGE	
1U rack mount kit included with XTM 330 only		
100-240 VAC Autosensing		
U.S. 50 Watts (171 BTU/hr)		
U.S. 24.0 Watts (82 BTU/hr)		
U.S. 23.33 Watts (80 BTU/hr)		
16.1 lbs (7.3 Kg)		
3.2 lbs (1.45 Kg) / 3.6 lbs (1.6 Kg)		
18" x 21" x 5.25" (45.7 x 53.3 x 13.3 cm)		
10.75″ x 13.25″ x 3.4″ (27.3 x 33.7 x 8.6 cm)		
11.25" x 17" x 1.75" (28.6 x 43.2 x 4.5 cm)		
7.75″ x 10.75″ x 5″ (19.7 x 27.3 x 12.7 cm)		
6.1″ x 7.5″ x 1.25″ (15.5 x	19.0 x 3.2 cm)	
	7.75" x 10.75" x 5" (19.7 x 11.25" x 17" x 1.75" (28.6 10.75" x 13.25" x 3.4" (27. 18" x 21" x 5.25" (45.7 x 5 3.2 lbs (1.45 Kg) / 3.6 lbs 16.1 lbs (7.3 Kg) U.S. 23.33 Watts (80 BTU/I U.S. 24.0 Watts (82 BTU/I U.S. 50 Watts (82 BTU/I U.S. 50 Watts (171 BTU/h 100-240 VAC Autosensin 1U rack mount kit includ <b>OPERATING</b> 32° F to 104° F 0° C to 40° C 32° F to 104° F 0° C to 40° C 10% to 85% non-condensing 0 to 9,843 ft @ 95° F (3,000 m @ 35° C) 0 to 9,843 ft at 95° F (3,000 m at 35° C)	

# **EXPERT GUIDANCE AND SUPPORT**

A subscription to LiveSecurity<sup>®</sup> Service is included with every XTM 3 appliance for hardware warranty, technical support, and software updates. Renewable in multi-year subscriptions.

# **BUY THE BUNDLE AND GET THE WORKS!**

Get everything you need for complete threat management at a great price with the Security Bundle. Includes XTM 3 Series appliance and subscriptions to Application Control, Gateway AV, spamBlocker, WebBlocker, Intrusion Prevention Service, Reputation Enabled Defense, and LiveSecurity.\*\* A great deal when you buy together and save!

\*\*XTM 33/33-W Bundle includes standard LiveSecurity with 12/5 tech support. XTM 330 Bundle includes Livesecurity Plus with 24/7 tech support.

\*Throughput rates will vary based on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network.

www.watchguard.com

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.6613.0895 www.watchguard.co No express or implied waranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2013 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Fireware, and LiveSecurity are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE66745\_010913

01.15